

FS 3403 VRG - Scouring machine for building renovation

110V - Part No. TBA

220V - Part No. 333.611



Scouring machine for building renovation work

- VR microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- Vacuum hood: with stepless height adjustment
- Sturdy milling discs: from high quality carbide
- Vacuum attachment
- Adjustable speed makes it suitable for a wide range of tasks: stripping plaster, milling away concrete shuttering protrusions, touching up small repair areas on thermal insulation facades
- The tool has 2 handles, allowing optimum control and operation: shaft handle with switch-on lock and bow handle

TECHNICAL DATA

Technical attributes	FS 3403 VRG
Milling head Ø	85 mm
Working width	76 mm
Max. milling depth	5 mm
Speed without load	1100-3700 rpm
Power input	1400 watt
Power output	880 watt
Weight	3,00 kg

Standard equipment	
12 flat tooth milling disc	333.719
1 bail handle	298.506
1 universal adapter	259.827
1 hexagon socket screw key	1 piece
1 Torx-wrench	1 piece
1 metal carrying case	334.073

Carbide pointed tooth milling discs



12 flat milling discs for replacement, made of solid carbide alloy. For light, soft plaster. Also for removing carpet adhesive residues when a clean, smooth base is required.

QTY/PKG: **Order no.**

12 **333.719**



12 pointed milling discs for replacement, made of solid carbide alloy. For removing hard plaster and cement. For removing carpet adhesive residues when a roughened base is required.

QTY/PKG: **Order no.**

12 **333.700**

Milling head complete



To switch quickly from sharp to flat milling discs. Complete with twelve flat HM milling discs (order number 333.719).

QTY/PKG: **Order no.**

1 **333.697**

To switch quickly from flat to sharp milling discs. Complete with twelve sharp HM milling discs (order number 333.700).

QTY/PKG: **Order no.**

1 **333.689**

