








# Grinding Guide

	Part No.	Bond	Applications
	365.5495L (left) Gold	Barracuda™ Max (LH and RH)	Quick removal of adhesive and coatings. Flattening of bumpy concrete surface. Removal of asphalt topping.
	365.5495R (right) Gold	Barracuda™ Max (LH and RH)	Quick removal of adhesive and coatings. Flattening of bumpy concrete surface. Removal of asphalt topping.
	365.5501 Black	XP1 (Soft Bond)30/40 grit	Single segment, for extremely hard concrete. First step grinding and levelling of slightly rough or uneven concrete floors.
	365.5502 Red	XP2 (Normal Bond)30/40 grit	Single segment, universal. First step grinding and levelling of slightly rough or uneven concrete floors.
	365.5503 Blue	XP3 (Hard Bond)30/40 grit	Single segment, for new and soft concrete. First step grinding and levelling of slightly rough or uneven concrete floors.
	365.5504 Brown 365.5506 Silver	XP4 - 50/60 grit XP6 - 60/70 grit	Single segment, (Terrazzo) Step 2 grinding to remove the scratches after using XP-1 or XP-3.
	365.5501/2 Black	XP1 (Soft Bond)30/40 grit	Double segment, for extremely hard concrete. First step grinding and levelling of slightly rough or uneven concrete floors.
	365.5502/2 Red	XP2 (Normal Bond)30/40 grit	Double segment, universal. First step grinding and levelling of slightly rough or uneven concrete floors.
	365.5503/2 Blue	XP3 (Hard Bond)30/40 grit	Double segment, for new and soft concrete. First step grinding and levelling of slightly rough or uneven concrete floors.
	365.5504/2 Brown 365.5506/2 Silver	XP4 - 50/60 grit XP6 - 60/70 grit	Double segment, for Terrazzo Step 2 grinding to remove the scratches after using XP-1 or XP-3.
	365.5510 Green	HP10 - 100 grit	Universal. Grinding and polishing of concrete floor after using XP-6.
	365.5515 Steel Blue	HP15 - 150 grit	Universal. Grinding and polishing of concrete floor after using XP-6.
	365.5520 Violet	HP20 - 200 grit	Universal. Wet grinding is recommended.
	365.5530 Orange	HP30 - 300 grit	Universal. Wet grinding is recommended.
	365.5540 Golden rod	HP40 - 400 grit	Universal. Wet grinding is recommended.
	365.5560 White	HP60 - 600 grit	Universal. Wet grinding is recommended.
	365.5710		Mounting plate for segments (Flower centre)
	365.5720		Mounting plate for segments (Triangle centre)

# Grinding Guide



## Polishing Pads (Velcro fit)

Professional resin bound diamond-polishing pads.



Colour	Part No.	Bond	Applications
	365.5602 Red	PD-220	220 grit, universal, wet application. Polishing of terrazzo/concrete floor after using HP-40 or HP-60.
	365.5604 Yellow	PD-400	400 grit, universal, wet application. Polishing of terrazzo/concrete floor after using PD-220.
	365.5608 White	PD-800	800 grit, universal, wet application. Polishing of terrazzo/concrete floor after using PD-400.
	365.5618 Blue	PD-1800	1800 grit, universal, wet application. Polishing of terrazzo/concrete floor after using PD-800.
	365.5635 Grey	PD-3500	3500 grit, universal, wet application. Polishing of terrazzo/concrete floor after using PD-1800.
	365.5730		Mounting plate for Velcro fitting pads (Flower centre)
	365.5740		Mounting plate for Velcro fitting pads (Triangle centre)

## SCREWS

All diamond segment plates are complete with fixing screw

	TBC		Screw to fit barracuda segments Dimension: M6 x 10
	TBC		Screw to fit HP & XP segments Dimension: M6 x 16

## XP-2 Ring available

	365.4502	XP-2 Ring (Normal bond) 30/40grit	Three segments, universal - First step grinding and levelling of slightly rough or uneven concrete floors
	TBC		Screw to fit XP-2 Ring segments Dimension: M8 x 16