



## Vario-Giraffe® wall and ceiling sander

- VV electronic control: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- Using a unique telescopic system, the Vario-Giraffe® adapts to your needs. Length adjustable from 1330 mm - 1730 mm. Open telescope lock lever, pull out handle and close lever. Handle rotates through 360°
- Adjustable locking screw for telescopic extension
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance
- With round sanding head that can be exchanged with just a click
- Backing pad with hook and loop face
- Vacuum cleaning system: guard with a brush ring, flexible suction hose from the sanding head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX industrial vacuum cleaner, models S 36, S 47 and S 47 M
- The brush ring is spring-mounted so that the round sanding head accurately follows all uneven contours. This allows the head to be applied with fingertip precision and also prevents any dust escaping
- Effective dust extraction from between the brush ring and the sanding pad (round) and through the 10-hole extraction ports prevents premature clogging of the abrasive and promotes a healthy, dust-free working environment
- The articulating sanding head can be adjusted to every tilt and angle.
- Ideally suited for sanding plaster boards, solid Styropor insulation slabs, preparation for painting, polishing

*Available as a kit :*



# WST 700 VV – Vario-Giraffe® wall & ceiling sander- Accessories

## TECHNICAL DATA

Technical attributes	WST 700 VV
Power input	710 watt
Power output	420 watt
Speed without load	1000-1500 rpm
Dimensions in mm	1330-1730
Weight	4,80 kg

## Standard equipment

Round sanding head	350.346
Velcro sand paper, grit 60	1 item from 348.503
Velcro sand paper, grit 80	1 item from 348.511
Velcro sand paper, grit 100	1 item from 348.538
Velcro sand paper, grit 220	1 item from 348.546
4 m vacuum hose, 32 mm Ø with positive-lock connector and vac connection, antistatic.	354.953
Padded carry case	1 piece

### Velcro abrasive paper, Select, round



For grinding joint filler in drywall construction, punched for dust extraction.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
-------------------	-------	----------	-----------

225 Ø	grit 16	10	350.079
-------	---------	----	---------



For grinding joint filler in drywall construction, punched for suction and dust extraction

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
-------------------	-------	----------	-----------

225 Ø	grit 40	25	350.087
225 Ø	grit 60	25	348.503
225 Ø	grit 80	25	348.511
225 Ø	grit 100	25	348.538
225 Ø	grit 120	25	349.216
225 Ø	grit 150	25	349.224
225 Ø	grit 180	25	349.232
225 Ø	grit 220	25	348.546

### Round sanding head



Optimally suitable for finishing large surfaces on walls and ceilings. Effective dust extraction, high surface removal rate.

QTY/PKG:	Order no.
----------	-----------

1	350.346
---	---------

## Velcro backing pad Ø 225, round

---



Hard backing pad with high removal rate, with use with hook and loop backed abrasives

QTY/PKG:    Order no.

---

1            350.362



Soft backing pad with high removal rate, with use with hook and loop backed abrasives.

Order no.

---

352.306

## Storage system for S 47, S 47 M

---



Fits on to the industrial vacuum cleaner for the WST 700 VV Giraffe® or MS 1706 FR wall chaser and vacuum hose.

QTY/PKG:    Order no.

---

1            350.370

## Anti-static vacuum hose

---



4 m vacuum hose, 32 mm Ø with positive-lock connector and vac connection, antistatic.

QTY/PKG:    Order no.

---

354.953

# WST 700 VV – Vario-Giraffe® wall & ceiling sander- Applications

